US-562/BIS

Carro auxiliar transportador carrocería

Auxiliry trolley body transporter

1200 Kg	600 mm	300 mm	1880 mm	200 mm





Para el desplazamiento de carrocerías desprovistas de mecánica tanto anterior como posterior. Lo mismo sucede en el caso de que la carrocería esté desprovista de mecánica con el empleo de dos carros. El gran diámetro de sus ruedas, hacen que el desplazamiento sea fácil. Puede ser movido dentro de la cabina de pintura, sin que las ruedas sufran ningún desperfecto. Siendo éstas de naylon, soportan tranquilamente una temperatura entre 90 y 100 grados.

The moving of vehicles without front or rear mechanics is no longer problem.The same results is obtained also if the vehicle is without both front and rear mechanics, by using two trolleys. The diameter of the four rotating wheels used for the trolley makes it easy. It is important to point out that the trolley can be left in the painting ovens without uffering any damage to the wheels. In fact, being wheels in nylon, they can withstand temperatures up to 90 and 100 centigrade degrees..

US-1190/12

Bead Bazooka - Calderín auxiliar. 12L

Bead Bazooka - Auxiliary boiler. 12L

Volumen - Volume	12 L
Presión - Pressure	10 Bar
Motocicleta - Motorcycle	
Coche - Car	•
Furgoneta - Van	•
Camión - Truck	•
Peso - Weight	5 kg

